

Everhard's drain Matting is 150g/m<sup>2</sup> non woven polyester geotextile. It is ideal for waste water disposal trenches, stormwater drainage systems, retaining walls and absorption trenches.

PROPERTIES	STANDARD	UNIT	TEST RESULT
Material			Polyester
Thickness	ASTM D 5199	mm	2.00
Average weight	ASTM D 5261	gsm	150.00
Grab Tensile Strength-MD	ASTM D 4632	N	175.30
Grab Tensile Strength-CD	ASTM D 4632	N	160.30
Grab Tensile Elongation-MD	ASTM D 4632	%	75.86
Grab Tensile Elongation-CD	ASTM D 4632	%	86.97
CBR Plunger Strength	ASTM D 6241/ AS 3706.4	N	330.27
UV Stability (@500hrs)	ASTM D 4355	%	85.00
UV Stability (@2500hrs)	ASTM D 4355	%	75.00



Product Code		
82069	6 metres x 600mm (Sold in box lots of 12)	0.54 ea
82070	6 metres x 2 metres (Sold in box lots of 4)	1.80 ea
82061	600mm wide x 50 metre roll	3.6
82067	1200mm wide x 50 metre roll	7.2
82068	2m wide x 50 metre roll	12
82069	600mm wide x 6 metre roll	.5
82070	2m wide x 6 metre roll	1.8

Disclaimer: All measurement are in millimetres and are solely for reference purposes. Colours have been reproduced with as much accuracy as possible. Any changes resulting from technical advance of design or colour may be made without prior notice. Tapware, accessories and appliances are for illustration purposes only. Further information on warranties is available at [www.everhard.com.au](http://www.everhard.com.au)

Version: 001